

Sitescan D-50 - Full Specifications

GENERAL PHYSICAL CHARACTERISTICS	
Dimensions (W x H x D)	238 x 172 x 70mm
Weight (with battery)	1.3 kg (2.4 lb.)
UT ports	1 TX/RX - 1 RX
UT Connectors	LEMO 1 or BNC
Encoder	LEMO 4-pin
USB Connection	Internal storage shown as memory device
Video output	Factory option
POWER AND CHARGING	
Battery Type	1 Li-ion battery pack, 14.8V nominal Capacity: 4.4 Ah
Maximum Power consumption	20 W (1.33 A at 15 V)
Operation	On battery
Battery Replacement	Yes - no tools required
Battery Recharge	Rechargeable in unit, and standalone charge using specified charger.
External Power	15Vdc supply
Battery Life	Typical 10.5 hours of continuous work
Charger	100-240V 50-60Hz
DISPLAY	
Type	LCD, TFT
Size	117 x 87 mm
Resolution	640 x 480 pixels (full VGA)
Ascan Area	Normal: 92.5 x 73 mm (510 x 402 pixels) Full: 116 x 77.5 mm (640 x 427 pixels)
Colours	8 colour options with variable brightness
Polarizer	Anti-glare
Backlight	LED
High Contrast Mode	Yes (sunlight readable)
Screen refresh rate	60Hz (NTSC only) 200MHz (time resolution= 5nS)
Maximum digitization frequency, no processing	200 MHz (processing is by FPGA)
Digitization frequency with processing	200 MHz (processing is by FPGA)
Digitizer vertical resolution	10 bits
Digital, Response time	Equal to 1/PRF
PULSER	
Pulser Type	Square Wave negative pulse
Pulse Voltage	Fixed 200V
PRF	Adjustable 35Hz to 1kHz.
Rise/Fall Time	<15nS into 50R load
Damping	50 and 400 Ω damping selectable
RECEIVER	
Gain range	0 to 110 dB
Maximum Input Voltage	Double probe: 13 Vpp (clamping level)

Filters	Single probe: 32 Vpp (clamping level)
Receiver Mode	1 broadband 1MHz to 16 MHz
Rectification	Pulse-Echo, transmit/receive
Signal Reject Type	Full, Positive Half, Negative Half, RF
Signal Reject Level	None, Suppressive, Linear
Smoothing	0% to 80%
Reference A-Scan	Off, Smooth and Fil
A-Scan %FSH Range	Yes (live)
Analog to Digital Conversion	0% to 180% FSH (without suppressive reject)
System Linearity	10 bits per sample, 200 MHz sampling rate
	Vertical < 2% Full Screen Height (FSH).
	Horizontal +/- 0.2% - 0.5% Trace Full Screen Width (FSW). (dependent on range)
A-SCAN PRESENTATION	
A-Scan Trace	Thin, Thick Filled
Rulers	Vertical (%FSH) and horizontal (distance or time)
Grid Type	None, On, Solid, Sparse, 50% (dotted), 1/2 skip
Grid Alignment	Fixed (10 divisions)
Overlay Mode (Skips)	1/2 Skip and 1/2 Skip+
Zoom in Gate	Yes
Freeze	Yes – All measurements and gates remain active
A-Scan Capture	Yes – (full resolution, includes scan parameters and measurements)
GATES AND MEASUREMENTS	
Number of Gates	2
IFT	Yes (Option)
Gate Measurements	7 measurement modes: Signal Monitor, Depth, Echo-Echo, Trigonometric, Gate to Gate, Flank to Flank and Beam angle
Gate Triggering	Peak, Flank, First Peak
Gate to Gate Measurements	Yes, all modes (Peak, Flank, First Peak)
DAC	Yes, 20 reference points with 3 custom curves (standard)
DAC Measurements	Relative or Absolute, in % or dB
TCG	Yes – with DAC to TCG and TCG to DAC (option)
Split DAC	Yes (Option)
DGS/AVG	Yes (Option)
AWS	Yes (Option)
BEA	Yes (Option)
Corrosion/TLog	Yes (Option)
Active Edge™	Unique Active edge mode for improved near surface resolution.
API	Yes (Standard)
Alarms	2
Alarm sources	G1, G2, DAC.
Measurement Display	Live display and updates on screen 10 times per second
USER CALIBRATION	
Units	Metric (mm), Imperial (in)
Auto Cal	2-point calibration, Zero, Velocity
Velocity	1000 – 10000 m/s
Range	1 to 10000 mm
Zero Offset (Probe Zero)	0 to 999.995 µs
Delay	0 to 9999 mm

MEMORY AND STORAGE	
Total Memory	4 GB
Thickness Logging with A-Scan Storage	450,000 Panels, 200,000 A-Logs, 300,000 B-Charts, 440,000 T-Logs
ENVIRONMENTAL	
IP Rating	Designed to meet IP67
Vibration Tested	MIL-STD-810F, Method 514.5, Procedure I
Shock Tested	MIL-STD-810F, Method 516.5, Procedure I
Explosive Atmospheres	MIL-STD-810F, Method 511.5, Procedure I
Operating Temperature	-10 °C to 55 °C
Storage Temperature	-40 °C to 75 °C (Battery is -20 °C to 60 °C)

All above specifications subject to change without notice